

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A fluid driven lighting system, comprising:

a showerhead configured within a housing, the showerhead including a flat, disc-shaped dispersing portion having ports formed to eject water in a spray suitable to wash an entire human body positioned beneath the dispersing portion;

~~a rechargeable battery;~~

one or more lights fixed within the housing such that beams from the one or more lights are directed down into a region beneath the dispersing portion such that the beams provide pleasant visual effects upon a person located beneath the showerhead;

and

a fluid driven power supply in electrical communication with ~~[[the]]~~ a rechargeable battery and the one or more lights, the fluid driven power supply configured to receive incoming fluid and release outgoing fluid to the showerhead so as to charge the rechargeable battery and light the one or more lights.

2. (original) The system according to claim 1, wherein the fluid driven power supply is a water driven turbine that includes:

a housing having an internal fluid path with a fluid inlet and a fluid outlet;

a rotatable turbine wheel positioned in the internal fluid path;

a generator positioned proximate the housing; and

a turbine shaft connecting the rotatable turbine wheel and generator.

3. (original) The system according to claim 2, wherein the housing further includes a fluid flow valve.

4. **(cancelled)**
5. **(original)** The system according to claim 1, wherein the one or more lights produce one or more colors.
6. **(original)** The system according to claim 1, wherein the one or more lights illuminate fluid released by the showerhead.
7. **(original)** The system according to claim 1, wherein the one or more lights comprise one or more light emitting diodes.
8. **(original)** The system according to claim 1, wherein the showerhead is formed from a translucent material.
9. **(original)** The system according to claim 8, wherein the one or more lights are integral to the translucent material.
10. **(original)** The system according to claim 8, wherein the one or more lights illuminate the translucent material.
11. **(original)** The system according to claim 8, wherein the translucent material forms an optical lens element.
12. **(currently amended)** An illuminating showerhead assembly comprising:
 - a hollow body formed from a translucent material, the hollow body being configured to receive incoming fluid and to release outgoing fluid;
 - a rechargeable battery proximate to the hollow body;
 - a showerhead within the hollow body, the showerhead including a flat, disc-shaped dispersing portion having ports formed to eject water in a spray suitable to wash an entire human body positioned beneath the dispersing portion;

one or more lights attached to the hollow body such that beams from the one or more lights are directed down into a region beneath the dispersing portion such that the beams provide pleasant visual effects upon a person located beneath the showerhead;
and

a fluid driven power supply in electrical communication with the rechargeable battery and the one or more lights, the fluid driven power supply configured to receive inlet fluid from a fluid source and release fluid to the hollow body so as to charge the rechargeable battery and light the one or more lights.

13. **(original)** The assembly according to claim 12, wherein the fluid driven power supply comprises a water driven turbine having:

- a housing having an internal fluid path with a fluid inlet and a fluid outlet;
- a rotatable turbine wheel positioned in the internal fluid path;
- a generator positioned proximate the housing; and
- a turbine shaft connecting the rotatable turbine wheel and generator.

14. **(cancelled)**

15. **(original)** The assembly according to claim 12, wherein the one or more lights are integral to the hollow body.

16. **(original)** The assembly according to claim 12, wherein the one or more lights illuminate fluid released by the hollow body.

17. **(original)** The assembly according to claim 12, wherein the one or more lights comprise one or more light emitting diodes.

18. **(original)** The assembly according to claim 12, wherein the one or more lights illuminate the hollow body.

19. **(currently amended)** A water fixture comprising:

a water inlet formed in a housing;

a water outlet formed in the housing;

~~a rechargeable battery~~ a showerhead within the housing, the showerhead including a flat, disc-shaped dispersing portion having ports formed to eject water in a spray suitable to wash an entire human body positioned beneath the dispersing portion;
one or more lights fixed within the housing such that beams from the one or more lights are directed down into a region beneath the dispersing portion such that the beams provide pleasant visual effects upon a person located beneath the showerhead;
and

an inline water driven power supply located between the water inlet and the water outlet; the inline water driven power supply being configured to receive an incoming water flow from the water inlet, generate electrical power from the incoming water flow, supply the electrical power to ~~[[the]]~~ a rechargeable battery so as to charge the rechargeable battery, and release an outgoing water flow to the water outlet.

20. **(original)** A water fixture according to claim 19, wherein the inline water driven power supply comprises:

a housing having an internal fluid path configured to receive the incoming water flow and release the outgoing water flow to the water outlet;

a rotatable turbine wheel positioned in the internal fluid path;

a generator positioned proximate the housing; and

a turbine shaft connecting the rotatable turbine wheel and generator.

21. **(cancelled)**

22. **(original)** A water fixture according to claim 19, further comprising one or more lights powered by the inline water driven power supply.

23. **(original)** A water fixture according to claim 22, further comprising a translucent

showerhead located between the water inlet and the water outlet, wherein the one or more lights illuminate the translucent showerhead.

24. **(original)** A water fixture according to claim 22, further comprising a showerhead located between the water inlet and the water outlet, wherein the one or more lights illuminate outgoing fluid emitted from the showerhead.